

3.4 Current Monitoring

MRI32R

3 phase | 2 CO | current monitoring



Power supply

Nominal voltage	12 ... 48 V AC / DC	110 ... 240 V AC / DC
Operating voltage range	10 ... 60 V	85 ... 250 V
Power consumption AC / DC	3.2 VA / 1.6 W	2.6 VA / 1.5 W
Rated frequency	16 ... 63 Hz	16 ... 63 Hz

Measuring circuit

Measured parameters	I, f
Min. setting step, resolution	0.1 A / 1 Hz
Monitoring functions	Under, over, inside, outside
Number of voltage measurement inputs	3
Rated measurement current	5 A
Measurement current range	0.1 ... 5 A
Underrun current setting range	0.1 ... 6 A
Overshoot current setting range	0.1 ... 6 A
Rated base frequency	15 ... 150 Hz
Alarm delay	0.5 ... 999.9 s
Alarm reset delay	0.5 ... 999.9 s

Main circuit

Number of contacts	2 CO
Available contact materials	AgNi
Rated voltage	250 V AC
Rated current	6 A
Minimum load	10 mA, 10 V
Inrush current	10 A, 10 ms
Rated load DC	fig. 2
Rated load AC-1	1,250 VA
Mechanical endurance (cycles)	30 000 000
Electrical endurance at rated load AC-1 (cycles)	fig. 3

Insulation

Rated test voltage measuring / measuring circuit	1.5 kV rms / 1 min
Rated test voltage measuring circuit / power supply	2 kV rms / 1 min
Rated test voltage measuring circuit / main circuit	2 kV rms / 1 min
Rated test voltage main circuit / power supply	2 kV rms / 1 min
Rated test voltage main / main circuit	1.5 kV rms / 1 min
Rated test voltage open contact	1.5 kV rms / 1 min
Pollution degree	2
Overshoot category	III

General data

Ambient temperature storage (no ice)	-40 ... 85 °C
Ambient temperature operation	-40 ... 60 °C
Conductor cross section	2.5 mm ²
Nominal screw torque	0.6 Nm
Dimension	fig. 4
Weight	125 g
Protection degree	IP 20
Housing material	PC

Product references

Description	Type	12	110
Three phase monitoring	MRI32R/UC...V	✓	✓

Other voltages on request. Please contact support@comatreleco.com.
"..." list control circuit voltage to complete product references.



fig. 1. Wiring diagram




fig. 2. AC voltage endurance




fig. 3. DC load limit curve





fig. 4. Dimension (mm)



Technical approvals, conformities

Standards EN 60730-1; EN 60947; EN 61000-6-2; EN 61000-6-3

Approvals CE cUL us EAC